



## Guarantee and Warranty Terms

(04/2022)

### 1) Guarantee

#### Conditions:

**All guarantees quoted below apply only if the emergency light power device is commissioned and the legally required annual function inspections and maintenance work are performed and documented by an authorized provider.**

#### LED lights are guaranteed for 50,000 hours or 5.7 years

din - Dietmar Nocker Sicherheitstechnik GmbH & Co KG guarantees for all lights that are integrated with din-LED-Laser technology in combination with either PLC24-, ILS, ILS-D, S3, SC CMR or DST electronics that 50,000 hours or 5.7 years will be maintained (max. 50,000 hours or 5.7 years + 4 months after delivery), provided the following conditions are met:

- The lights may be operated only at approved locations. (see technical data in the operating manual)
- The guarantee applies to the entire light (housing, LED module, PLC24, ILS, ILS-D, S3, SC CMR, central monitored radio control or DST electronics). For single-battery lights (sc AT - self-contained automatic test), the 50,000-hour guarantee applies only to built-in LEDs. The single-battery accumulator is expressly excluded from the 50,000-hour guarantee.
- Visible deviations from published electrical or optical specifications – for example, a decrease in light intensity or a change in the colour of the light – are considered normal and are not covered by these guarantees.
- din - Dietmar Nocker Sicherheitstechnik GmbH & Co KG guaranteed that after 50,000 hours at least 70% of the original light intensity will still remain, provided the lights are operated in the authorised temperature ranges. (see technical data in the operating manual)
- All technical planning data for the lights are calculated with reserves for the standardised lighting in the pictogram surfaces, whereby the standard conformity is also achieved in case of light emissions up to 70%.
- In case of a guarantee claim, din - Dietmar Nocker Sicherheitstechnik GmbH & Co KG shall provide the LED replacement set free of charge.

#### 50,000 hours or 5.7 year guarantee for emergency power devices in the SU series, din battery systems (DBS), and BASIC-DST systems, including a safety power source and DFS E30 housing

din - Dietmar Nocker Sicherheitstechnik GmbH & Co KG guarantees for all systems (including safety power source) of the SU series (SU.20, SU.40, SU.80, SU.net, SU.net E30), of the DBS series (din battery systems including safety power source, and DFS E30 housing), and the BASIC-DST series that 50,000 hours or 5.7 years will be maintained (max. 50,000 hours or 5.7 years + 4 months after delivery), provided the following conditions are met:

- The emergency power devices may be operated within the authorized environments and temperature ranges. (see technical data in the operating manual)
- The din safety power sources are enclosed lead batteries that must be operated in the temperature range 20 °C ± 10% and used according to ÖVE/ÖNORM E 8002, OVE E 8101, EN 50171 ÖVE/ÖNORM EN 50272-2, and OVE EN IEC 62485-2. The capacity must be adjusted as required by the standard to suit the temperatures at the set-up location.
- din safety power sources are LiFePO<sub>4</sub>, lithium iron phosphate batteries must be operated in environmental temperature range from +10 °C to +35 °C and used according to EN 50171. The capacity must be adjusted to suit the temperatures at the set-up location.
- During commissioning/initial installation, the din safety power source must be charged completely.
- No interruption to the charge of the din safety power sources over a period longer than 4 months in the completely charged condition
- After discharging the din safety power sources, a complete charge must follow immediately afterwards
- The DFS E30 fire protection housings are only combined with components defined according to the test certificate and have been set up in accordance with the available DFS E30 assembly and operating manual.
- The emergency light power device and the DFS E30 housing are maintained according to legal regulations by a din service technician, but at least once per year. (one-time legal maintenance, legal maintenance with the din maintenance agreement, extended legal maintenance with din maintenance agreement)
- din - Dietmar Nocker Sicherheitstechnik GmbH & Co KG guarantees according to legal regulations at the time of commissioning that the entire system will remain completely functional for the specified duration of 50,000 hours or 5.7 years. (adherence to the autonomous time, technical functionality, etc.)
- In case of a guarantee claim, din - Dietmar Nocker Sicherheitstechnik GmbH & Co KG shall provide repairs free of charge or an equivalent replacement device. Possible disassembly, assembly, and other subsequent costs and auxiliary costs are not included in the guarantee.



### Guarantee for din safety power sources

In case of din safety power sources as LiFePO<sub>4</sub>, i.e. lithium iron phosphate batteries, that are operated in combination with an SU system or installed in these systems as a replacement safety power source, din-Dietmar Nocker Sicherheitstechnik GmbH & Co KG generally guarantees 50,000 hours or 5.7 years from commissioning (max. 50,000 hours or 5.7 years + 4 month from delivery), provided the following conditions are met:

- During commissioning/initial installation, the din safety power source must be charged completely.
- No interruption to the charge over a period longer than 4 months in the completely charged condition
- After discharging the safety power sources, a complete charge must follow immediately afterwards
- din safety power sources must be operated in environmental temperature range from +10 °C to +35 °C and used according to EN 50171. The capacity must be adjusted to suit the temperatures at the set-up location.
- Commissioning the emergency power device in case of new safety power sources or installation and calibration according to the manufacturer's specifications for replacement safety power sources, all completed by a din service tech.

In case of din safety power sources as enclosed lead batteries that are operated in combination with an SU series or operated in a din battery system (DBS) or installed in these systems as a replacement safety power source, din-Dietmar Nocker Sicherheitstechnik GmbH & Co KG generally guarantees 3 years from commissioning (max. 3 years + 4 months from delivery), provided the following conditions are met:

- During commissioning/initial installation, the din safety power source must be charged completely.
- No interruption to the charge over a period longer than 4 months in the completely charged condition
- After discharging the safety power sources, a complete charge must follow immediately afterwards
- The din safety power sources must be operated in the temperature range 20 °C ± 10% and used according to ÖVE/ÖNORM E 8002, OVE E 8101, EN 50171 ÖVE/ÖNORM EN 50272-2, and OVE EN IEC 62485-2. The capacity must be adjusted as required by the standard to suit the temperatures at the set-up location.
- Commissioning the emergency power device in case of new safety power sources or installation and calibration according to the manufacturer's specifications for replacement safety power sources, all completed by a din service tech.

Li-Ion, NiCd, and NiMh batteries are guaranteed for 1 year.

All items from CEAG/EATON are excluded from the guarantee.

### The guarantee does not cover:

- Any incidental expenses that arise in connection with the guarantee such as, for example, costs of assembly and disassembly, shipping or disposal fees, travel- or transit time, lifting equipment, scaffolding, etc.
- Items such as laptop computers, PC hard drives, and printers are excluded from the din-Sicherheitstechnik guarantee. Legal guidelines apply.

**The guarantee is terminated immediately upon any hardware or software modifications or alterations undertaken without written permission from din - Dietmar Nocker Sicherheitstechnik GmbH & Co KG, or if the emergency light power device is maintenance or service incorrectly.**

## 2) Warranty

In general, certain legally-binding terms of the warranty go into effect after the contract is signed.

### Warranty Restrictions Based on Statutory Provisions:

Please note that an emergency-lighting installation is considered to be an engineered safety feature, for which the legislature has stipulated a schedule of inspections and maintenance to assure safe operation. Refer to the following regulations in this case: Workplace Directive, technical information for workplaces, OIB Directives, OVE E 8101, OVE Directive R12-2, ÖVE/ÖNORM E 8002, ÖVE/ÖNORM 50171, ÖVE/ÖNORM EN 50172, ÖVE/ÖNORM EN 50272-2, OVE EN IEC 62485-2, ÖNORM EN 1838, ÖVE/ÖNORM EN 62034, building permission, and fire protection concept

In general, warranty claims will be considered only if the following conditions are met:

- Inspections legally required as part of initial start-up, restarts, or for ongoing operation must be done thoroughly and a complete record of them kept. (documentation conforms to Section 9.3 of ÖVE/ÖNORM E 8002 Item 56.NE.560.6.500.9 and National Amendment 1.NE of OVE E 8101 or "Electrical Findings of the Federal Guild of Electrical Engineers", Survey, Inspection, Measurement: Security Lighting, 04-2004)
- Pursuant to OIB Directives, OVE E 8101, ÖVE/ÖNORM EN 62034, ÖVE/ÖNORM EN 50172, and ÖVE/ÖNORM E 8002 in Austria, functionality tests must be conducted and documented at statutory intervals.



- The legally required annual inspection and maintenance work as per the Workplace Directive, OIB Guidelines, OVE E 8101, ÖVE/ÖNORM EN 62034, ÖVE/ÖNORM EN 50172, ÖVE/ÖNORM EN 50171, OVE EN IEC 62485-2, ÖVE/ÖNORM EN 50272-2, and ÖVE/ÖNORM E 8002 must be completed by whoever sets up the system (authorised company) or by din-Dietmar Nocker Sicherheitstechnik GmbH & Co KG.
- Changes in the hardware and software of the emergency lighting power supply that are not carried out by din - Dietmar Nocker Sicherheitstechnik GmbH & Co KG, immediately invalidate all warranty claims for emergency power devices and lights. The event log stored in the emergency-lighting equipment serves as evidence of tampering.
- The operator must service and clean the emergency-lighting equipment, its components, electronics, lights, and safety power sources in accordance with regulations. Thick layers of dust on electronic components from drilling, plaster residues, moisture, etc. impair their ability to function and invalidate the warranty.
- Only the statutory warranty period applies to purchased parts like computer parts or printers.
- The guarantee applies as exclusive on the condition that the products are used in accordance with the specified product and application specifications (data sheet) and were professionally installed and commissioned (according to the assembly manual accompanying the product).
- The emergency light power device, the components, electronics, lights, and safety power sources may not be exposed to an aggressive, caustic atmosphere.
- Consumables such as NiCd batteries or lamps are excluded from warranty claims.
- A warranty claim is terminated immediately if devices or lights are altered or repaired without written consent from the manufacturer or if items are installed incorrectly or by unqualified personnel.

All CEAG/EATON items feature a 12-month guarantee from delivery.

In case of products with obvious transport damage, no claims originating from the guarantee/warranty shall be honoured. It must be ensured that received goods are checked for damage immediately upon acceptance so that possible transport damage may be credibly assigned to the courier.

Any incidental expenses that arise as a consequence of a deficiency (such as costs of assembly and disassembly; shipping of a faulty, repaired, or new product; waste disposal; travel- or transit time; lifting equipment and scaffolding) are not covered, unless such costs are communicated in advance and approved in writing by din - Dietmar Nocker Sicherheitstechnik GmbH & Co KG.

**The firm installing the facility must make the terms of the guarantee conditions known to the facility operator.**

### 3) Telematics log data

din - Dietmar Nocker Sicherheitstechnik GmbH & Co KG collects telematics data from running operation of the din system to visualise correct operation. The data are saved to ensure the quality and function of the din system and to increase the safety level on a correspondingly secured server of din - Dietmar Nocker Sicherheitstechnik GmbH & Co KG in Austria. Furthermore, maintenance activities are carried out by remote maintenance within the framework of newly concluded or already existing maintenance agreements, provided that the technical requirements and a safety-related added value for the user, operator or owner are given.

The telematics module possesses a CE declaration, conforms with standards and all applicable guidelines, and is officially approved. Any possible responsibility for resulting damages shall only be accepted in case of proof of blatantly gross negligence or intent.

The user, operator or owner of the system can object in writing both to the activation of the telematics module and to the remote maintenance of his din system.

In case of deactivation of the module, the current guarantee and guarantee conditions of Dietmar Nocker Sicherheitstechnik GmbH & Co KG shall nevertheless apply to the din system.

din - Dietmar Nocker Sicherheitstechnik GmbH & Co KG  
Kotzinastraße 5 - 7, A - 4030 LINZ  
**[www.notlicht.at](http://www.notlicht.at)**